

Cowan Heights Water System



About the Company

GSWC is a wholly owned subsidiary of American States Water Company (NYSE:AWR) and provides water service to over 1 million customers throughout 12 counties in Northern, Coastal and Southern California. American States Water Company also owns a contracted services subsidiary, American States Utility Services, Inc. (ASUS). ASUS provides operations, maintenance and construction management services for water and wastewater systems located on military bases throughout the country under 50-year privatization contracts with the U.S. government. Bear Valley Electric Service is also a subsidiary and distributes electricity to approximately 24,000 customers in the City of Big Bear Lake and surrounding areas in San Bernardino County.



Robert Sprowls
President and
Chief Executive Officer
Golden State Water Company



Ken Vecchiarelli General Manager, Orange County District Golden State Water Company

President's Message

Dear Golden State Water Customer,

Golden State Water Company (GSWC) is pleased to present our 2025 Annual Water Quality Report (Consumer Confidence Report), providing customers with important information regarding local water quality and service during the 2024 calendar year.

GSWC is proud to serve more than one million customers across 81 communities in California, delivering reliable, high-quality water every day. We know that access to safe water is essential, and our team works around the clock to ensure your water is always there when you need it.

From scientists and engineers to water quality experts, our dedicated team continuously monitors and tests for hundreds of potential contaminants to keep your water safe. By proactively testing for hundreds of potential contaminants in our water systems, GSWC has consistently scored among the top water companies for compliance with water quality regulations.

GSWC proudly reports that the water delivered to your tap meets all federal and state quality standards established to protect the public's health and safety.

This report provides information regarding local water supply sources, testing, and the steps GSWC takes to ensure our water complies with the strictest standards set by the United States Environmental Protection Agency (USEPA), State Water Resources Control Board's Division of Drinking Water (DDW), and California Public Utilities Commission (CPUC).

To access the most up-to-date Water Quality Report for your area, sampling results, and frequently asked questions, visit **www.gswater.com/water-quality**. If you have questions, please contact our 24-hour Customer Service Center at 1.800.999.4033 or email us at **customerservice@gswater.com**.

Given our proactive approach to maintaining, operating, and improving our water systems, our customers can rest assured that their monthly rates contribute directly to the safety and reliability of their local water system. This upholds the essential right of every Californian to access safe, clean, and affordable water, regardless of their zip code.

We encourage all customers to visit **www.gswater.com** and follow us on X (formerly Twitter) and Facebook at @GoldenStateH2O. On behalf of everyone at GSWC, thank you for allowing us to serve you and your community.

Sincerely,

Robert Sprowls

Ken Vecchiarelli

Robert J Apromle Kunith P. Vercherell.

Golden State Water is constantly working toward 100 percent customer satisfaction and we encourage you to visit www.gswater.com and follow us on Twitter and on Facebook at @GoldenStateH2O

Where Does **My Water** Come From?

Water delivered to customers in the Cowan Heights System is a blend of groundwater pumped

from the Orange County Groundwater Basin and imported water from the Colorado River Aqueduct and the State Water Project (imported and distributed by the Metropolitan Water District of Southern California). The Orange County Groundwater Basin stretches 350 square miles from the Orange County line at Seal Beach and Long Beach, along the coast down to the El Toro "Y" and east to Yorba Linda.



Source Water Assessment

Golden State Water Company conducted a source water assessment in 2020 for the groundwater well serving customers of its Cowan Heights System.

The groundwater source is considered most vulnerable to the following activities not associated with detected contaminants: confirmed leaking underground storage tanks and gas stations.

A copy of the assessment may be viewed at:

State Water Board Santa Ana District Office 2 MacArthur Place, Santa Ana, CA 92707

or

Golden State Water Company 2281 East Via Burton, Anaheim, CA 92806

You may request a summary of the assessment be sent to you by contacting:

State Water Board Santa Ana District Office at 1.714.558.4410

For more details, contact Roberto Casas, Associate Water Quality Engineer, at 1.800.999.4033, or email the Customer Service Center at customerservice@gswater.com.

In December 2002, the Metropolitan Water District of Southern California (MWD) completed a source water assessment of its Colorado River and State Water Project supplies.

Colorado River supplies are considered to be most vulnerable to the following: increasing urbanization in the watershed, recreation, urban/stormwater runoff, and wastewater.

State Water Project supplies are considered to be most vulnerable to the following: agriculture, recreation, urban/stormwater runoff, wastewater, and wildlife.

A copy of the assessment can be obtained by contacting MWD at 1.213.217.6000.



How to Read Your Table 5 Source Water Quality Table 5 Laboratory Analyses 6 Distribution Water Quality Table 6 Risk to Tap and Bottled Water 7 For Sensitive Immune Systems 7 Cross Connection Control Program 7 Flushing 7 Contact Us 8 Connect with Us 8 Infrastructure Investments 8 Conserving for California 8

CONTENTS

Glossary of Terms

Source Water Assessment

In every one of our water systems, a team of highlytrained employees monitors water quality on an on-going basis to ensure that our customers are receiving high-quality water. For more information and to access frequently asked questions about your 2024 CCR visit: https://gswater.com/ccrfaq





Delivering drinking water is serious business, and our team of scientists, engineers and water experts is dedicated to protecting our water systems and ensuring the water we deliver to local homes and businesses meets stringent standards set by the state and federal governments.



Glossary of Terms

Maximum Contaminant Level (MCL)

The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the public health goals and maximum contaminant level goals as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste and appearance of drinking water.

California Notification Level (NL)

Non-regulatory, health-based advisory levels established by the State Board for contaminants in drinking water for which an MCL has not been established.

Maximum Contaminant Level Goal (MCLG)

The level of a contaminant in drinking water below which there is no known or expected risk to health. Maximum contaminant level goals are set by the United States Environmental Protection Agency (USEPA).

Maximum Residual Disinfectant Level (MRDL)

The highest level of a disinfectant allowed in drinking water. There is convincing evidence that the addition of a disinfectant is necessary for control of microbial contaminants.

Maximum Residual Disinfectant Level Goal (MRDLG)

The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Primary Drinking Water Standard (PDWS)

MCLs, MRDLs and treatment techniques (TTs) for contaminants that affect health, along with their monitoring and reporting requirements.

Public Health Goal (PHG)

The level of a contaminant in drinking water below which there is no known or expected risk to health. Public health goals are set by the California Environmental Protection Agency (CalEPA).

Regulatory Action Level (AL)

The concentration of a contaminant which, if exceeded, triggers treatment or other requirements that a water system must follow.

Treatment Technique (TT)

A required process intended to reduce the level of a contaminant in drinking water.

| Unit of Measurement | Unit Abbreviation | Also Known as | This can be compared to | |
|-------------------------------|----------------------|--|--|--|
| Parts per million (PPM) | mg/L | milligrams per liter | 1 second in 12 days | |
| Parts per billion (PPB) | μg/L | micrograms per liter | 1 second in 32 years | |
| Parts per trillion (PPT) | ng/L | nanograms per liter | 1 second in 32,000 years | |
| Grains per gallon | grains/gallon | a measurement for water hardness often used for sizing household water softeners | 1 grain/gal equals 17.1 mg/L of hardness | |
| Nephelometric Turbidity Units | NTU | a measurement of the clarity of water | Turbidity in excess of 5 NTU is noticeable to the average person | |
| Microsiemens per centimeter | μS/cm | a measurement of a solution's ability to conduct electricity | | |
| Picocuries per liter | pCi/L | a measurement of radioactivity in water | | |

How to Read This Table

The highest level of a constituent allowed in drinking water.

The highest level for which the constituent has no known or expected health risks.

The consumer confidence report lets you know which constituents, if any, are in your drinking water and how this may affect your health. The constituents presented in this table were detected above the detection limit set by the State Water Resources Control Board. Below is a guide that explains each column of the table.

| The range of presence for wh the constituent was detected the drinking water. | ich in | The average amount of a constituent detected in the drinking water. | | | | ost recent Describes the most likely ways a constituent enters the drinking water. Wording provided by the USEPA. |
|---|-------------|---|-----------------------|------------------|------------------------------|---|
| | | | | | | |
| Primary Standards - Health Based (units) | Primary MCL | PHG (MCLG) | Range of Detection | Average Level | Most Recent Sampling Date | Typical Source of Constituent |
| Substance A (mg/L) | 50 | 0.6 | ND - 40 | 20 | 2019 | Erosion of natural deposits; residue from some surface water treatment processes |
| Substance B (μg/L) | 6 | 1 | 0.1 - 2.8 | 1.7 | 2016 | Discharge from petroleum refineries; fire retardants; ceramics; electronics; solder |

| YOUR WATER MEETS ALL CURRENT FEDERAL AND STATE REQUIREMENTS | | | | | | | | | | |
|---|-----------------------|---------------|-----------------------|------------------|------------------------------|---|--|--|--|--|
| Cowan Heights Water System – Source Water Quality | | | | | | | | | | |
| Primary Standards – Health Based (units) | Primary MCL | PHG (MCLG) | Range of Detection | Average Level | Most Recent Sampling Date | Typical Source of Constituent | | | | |
| Turbidity | | | | | | | | | | |
| Highest single measurement of the treated surface water (NTU) | TT = 1.0 | n/a | n/a | 0.06 | 2024 | Soil runoff | | | | |
| Lowest percent of all monthly readings less than 0.3 NTU (%) | TT = 95 | n/a | n/a | 100% | 2024 | Soil runoff | | | | |
| Inorganic Constituents | | | | | | | | | | |
| Aluminum (mg/L) | 1 | 0.6 | ND - 0.11 | ND | 2024 | Erosion of natural deposits; residue from some surface water treatment processes | | | | |
| Barium (mg/L) | 1 | 2 | ND - 0.12 | ND | 2024 | Discharges of oil drilling wastes and from metal refineries; erosion of natural deposits | | | | |
| Chromium, Hexavalent (µg/L) | 10 | 0.02 | ND - 0.25 | 0.12 | 2024 | Erosion of natural deposits; transformation of naturally occurring trivalent chromium to hexavalent chromium by natural processes an human activities, such as discharges from electroplating factories, leather tanneries, wood preservation, chemical synthesis, refractory production, and textile manufacturing facilities. | | | | |
| Fluoride (mg/L) | 2.0 | 1 | 0.20 - 0.80 | 0.45 | 2024 | Erosion of natural deposits; water additive that promotes strong teeth; discharge from fertilizer and aluminum factories | | | | |
| Nitrate [as N] (mg/L) | 10 | 10 | ND - 2.3 | 1.1 | 2024 | Runoff and leaching from fertilizer use; leaching from septic tanks and sewage; erosion of natural deposits | | | | |
| Radioactive Constituents | | | | | | | | | | |
| Gross Alpha Activity (pCi/L) | 15(a) | (0) | ND - 5 | ND | 2024 | Erosion of natural deposits | | | | |
| Gross Beta Activity (pCi/L) | 50(b) | (0) | ND - 5 | 4 | 2024 | Decay of natural and manmade deposits | | | | |
| Uranium (pCi/L) | 20 | 0.43 | ND - 3 | 1 | 2024 | Erosion of natural deposits | | | | |
| Secondary Standards – Aesthetic (units) | Secondary MCL | PHG (MCLG) | Range of Detection | Average Level | Most Recent Sampling Date | Typical Source of Constituent | | | | |
| Aluminum (µg/L) | 200 | n/a | ND - 110 | ND | 2024 | Erosion of natural deposits; residue from some surface water treatment processes | | | | |
| Color (units) | 15 | n/a | ND - 2 | 1 | 2024 | Naturally-occurring organic materials | | | | |
| Chloride (mg/L) | 500 | n/a | 78 - 116 | 92 | 2024 | Runoff/leaching from natural deposits; seawater influence | | | | |
| Odor—Threshold (units) | 3 | n/a | ND - 1 | ND | 2024 | Naturally-occurring organic materials | | | | |
| Specific Conductance (µS/cm) | 1600 | n/a | 725 - 1070 | 864 | 2024 | Substances that form ions when in water; seawater influence | | | | |
| Sulfate (mg/L) | 500 | n/a | 102 - 253 | 165 | 2024 | Runoff/leaching from natural deposits; industrial wastes | | | | |
| Total Dissolved Solids (mg/L) | 1000 | n/a | 446 - 686 | 555 | 2024 | Runoff/leaching from natural deposits | | | | |
| Other Parameters (units) | Notification Level | PHG (MCLG) | Range of Detection | Average Level | Most Recent Sampling Date | Typical Source of Constituent | | | | |
| Alkalinity (mg/L) | n/a | n/a | 105 - 159 | 134 | 2024 | | | | | |
| Calcium (mg/L) | n/a | n/a | 58 - 83 | 73 | 2024 | | | | | |
| Hardness [as CaCO3] (mg/L) | n/a | n/a | 235 - 305 | 262 | 2024 | The sum of polyvalent cations present in the water, generally magnesium and calcium; the cations are usually naturally occurring | | | | |
| Hardness [as CaCO3] (grains/gal) | n/a | n/a | 13.7 - 17.8 | 15.3 | 2024 | | | | | |
| Magnesium (mg/L) | n/a | n/a | 14 - 29 | 20 | 2024 | | | | | |
| pH (pH units) | n/a | n/a | 7.4 - 8.2 | 7.9 | 2024 | | | | | |
| Potassium (mg/L) | n/a | n/a | 2.2 - 5.4 | 3.6 | 2024 | | | | | |
| Sodium (mg/L) | n/a | n/a | 59.3 - 116 | 81.6 | 2024 | Refers to the salt present in the water and is generally naturally occurring | | | | |
| Unregulated Drinking Water Constituents (units) | Notification Level | PHG (MCLG) | Range of Detection | Average Level | Most Recent Sampling Date | | | | | |
| Perfluorobutanoic acid (PFBA) (ng/L) (c) | n/a | n/a | ND - 6.00 | ND | 2024 | | | | | |

(a) MCL is based on Gross Alpha minus Uranium. (b) DDW considers 50 pCi/L to be the level of concern for beta particles. (c) See the Perfluoroalkyl and Polyfluoroalkyl Substances (PFAS) section under Laboratory Analyses. ND = Not Detected CaCO3 = Calcium Carbonate

This table includes data only on constituents that were detected.

Laboratory Analyses

Through the years, we have taken thousands of water samples to determine the presence of any radioactive, biological, inorganic, volatile organic, or synthetic organic contaminants in your drinking water. The table we provide shows only detected contaminants in the water.

Even though all of the substances listed here are under the Maximum Contaminant Level (MCL), we feel it is important that you know exactly what was detected and how much of these substances were present in your water. Compliance (unless otherwise noted) is based on the average level of concentration below the MCL. The state allows us to monitor for some contaminants less than once per year because the concentrations do not change frequently. Some of our data, while representative, is more than a year old.

Chloramination — The water purchased by GSWC from the Metropolitan Water District of Southern California (MWD) contains chloramine. Chloramine is added to the water for public health protection. Chloraminated water is safe for people and animals to drink, and for all other general uses. Three special user groups, including kidney dialysis patients, aquarium owners, and businesses or industries that use water in their treatment process, must remove chloramine from the water prior to use.

Hospitals or dialysis centers should be aware of chloramine in the water and should install proper chloramine removal equipment, such as dual carbon adsorption units. Aquarium owners can use readily available products to remove or neutralize chloramine. Businesses and industries that use water in any manufacturing process or for food or beverage preparation should contact their water treatment equipment supplier regarding specific equipment needs.

Fluoridation — Fluoride has been added to the water that GSWC purchases from Metropolitan Water District of Southern California (MWD) since November 2007. Customers should see no difference in the taste, color or odor of their water as a result of fluoridation. Fluoridation does not change the way you normally use water for fish, pets or cooking. Parents and guardians of children who receive fluoride supplements should consult the child's doctor or dentist. For information regarding fluoridation of your water, please visit the Division of Drinking Water's fluoridation website at https://www.waterboards.ca.gov/drinking_water/certlic/drinkingwater/Fluoridation.html.

Lead — If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. GSWC is responsible for providing high quality drinking water but cannot

control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to two minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information about lead in drinking water, testing methods and steps you can take to minimize exposure is available from the USEPA's Safe Drinking Water Hotline at 1.800.426.4791 or at http://www.epa.gov/safewater/lead.

GSWC has completed the initial lead service line inventory required by the USEPA's Lead and Copper Rule Revisions. Through a thorough review of historical records and initial field investigations, GSWC has determined that its distribution systems do not have lead or galvanized service lines that require replacement. This includes any customer-owned service lines. For more information, please visit https://www.gswater.com/service-material-inventory.

Perfluoroalkyl and Polyfluoroalkyl Substances

(PFAS) — Per- and polyfluoroalkyl substances (PFAS) are a group of man-made chemicals that include Perfluorooctanoic Acid (PFOA), Perfluorooctane Sulfonate (PFOS), Perfluorobutane Sulfonic Acid (PFBS), Perfluorohexane Sulfonic Acid (PFHxS), Perfluorononanoic Acid (PFNA), and Hexafluoropropylene Oxide-Dimer Acid (HFPO-DA or Gen X).

While consumer products and food are a large source of exposure to these chemicals for most people, drinking water can be an additional source in the communities where these chemicals have infiltrated water supplies. Such contamination is typically localized and associated with a specific facility, including near groundwater recharge facilities where recycled wastewater is used; industrial facilities where these chemicals were produced or used to manufacture other products; an airfield at which they were used for firefighting; or wastewater treatment plants or landfills where products containing the chemicals were disposed of.

On April 10, 2024, the USEPA announced the final rule that sets the MCLs that range from 4 ppt to 10 ppt for six PFAS compounds: PFOA, PFOS, PFBS, PFNA, PFHXS, and HFPO-DA. In addition, the regulation also establishes a hazard index for PFAS mixtures. Public water systems are required to reduce PFAS levels below the MCL starting April 26, 2029.

Turbidity — Turbidity is a measure of the cloudiness of the water. It is monitored because it is a good indicator of the effectiveness of surface water filtration.

Unregulated Contaminant Monitoring — Monitoring for unregulated contaminants helps the USEPA and the State Water Resources Control Board to determine where certain contaminants occur and whether the contaminants need to be regulated.

| Cowan Heights Water System – Distribution Water Quality | | | | | | | | | | |
|---|-----------------------|----------------|---|------------------|------------------------------|--|------------------------------------|--|--|--|
| Disinfection Byproducts and Disinfectant Residuals (units) | Primary MCL (MRDL) | PHG (MRDLG) | Range of Detection | Average Level | Most Recent Sampling Date | Typical Source of Constituent | | | | |
| Bromate (µg/L) | 10 | 0.1 | ND - 1.6 | ND | 2024 | Byproduct of drinking water disinfection | | | | |
| Chlorine [as CI2] (mg/L) | (4.0) | (4) | 0.1 - 2.6 | 1.5 | 2024 | Drinking water disinfectant added for treatment | | | | |
| HAA5 [Sum of 5 Haloacetic Acids] (µg/L) | 60 | n/a | 2.9 - 12 | 19 | 2024 | Byproduct of drinking water disinfection | | | | |
| TTHMs [Total Trihalomethanes] (µg/L) | 80 | n/a | 4.4 - 43 | 43 | 2024 | Byproduct of drinking water disinfection | | | | |
| Inorganic Constituents (units) | Action Level | PHG (MCLG) | Sample Data | 90th % Level | Most Recent Sampling Date | Typical Source of Constituent | | | | |
| Copper (mg/L) | 1.3 | 0.3 | None of the 29 samples collected exceeded the action level. | 0.13 | 2022 | Internal corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives | | | | |
| Lead sampling in schools and residential plumbing | Action Level | PHG | Sample Data | 90th % Level | Most Recent Sampling Date | Typical Source of Constituent | Number of Schools Tested (d) | | | |
| Lead (µg/L) | 15 | 0.2 | None of the 29 samples collected exceeded the action level. | ND | 2022 | Internal corrosion of household water plumbing systems; discharges from industrial manufacturers; erosion of natural deposits. | 1 | | | |

(d) The State of California made lead sampling in schools mandatory with a compliance window through 2019. This table includes data only on constituents that were detected.

ND = Not Detected



Risk to Tap and Bottled Water

Drinking water, including bottled water, may reasonably be expected to contain small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the USEPA's Safe Drinking Water Hotline at 1.800.426.4791.

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the layers in the ground, it dissolves naturally occurring minerals and, in some cases, radioactive material, which can pick up substances resulting from the presence of animal or human activity.

In order to ensure that tap water is safe to drink, the USEPA and the State Water Resources Control Board prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. The U.S. Food and Drug Administration regulations and California law also establish limits for contaminants in bottled water that provide the same protection for public health.

Contaminants in Drinking Water Sources May Include:

- Microbial contaminants, such as viruses and bacteria, which may come from sewage treatment plants, septic systems, agricultural livestock operations and wildlife
- Inorganic contaminants, such as salts and metals, which can be naturally occurring or result from urban stormwater runoff, industrial or domestic wastewater discharges, oil and gas production, mining, and farming
- Pesticides and herbicides that may come from a variety of sources such as agriculture, urban stormwater runoff and residential uses
- Organic chemical contaminants, including synthetic and volatile organic chemicals, which are byproducts of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff and septic systems
- Radioactive contaminants that can be naturally occurring or be the result of oil and gas production and mining activities

For People with Sensitive Immune Systems

Some people may be more vulnerable to contaminants in drinking water than the general population. Immunocompromised people, such as those individuals with cancer undergoing chemotherapy, those who have undergone organ transplants, those with HIV/AIDS or other immune system disorders, some elderly populations, and infants, can be particularly at risk from infections. These people should seek advice from their health care providers.

The USEPA and Centers for Disease Control issue guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbial contaminants.

To obtain a copy of these guidelines, please call the USEPA's Safe Drinking Water Hotline at **1.800.426.4791**.

For additional information, please contact our 24-hour Customer Service Center at **1.800.999.4033** or email us at **customerservice@gswater.com**.

Cross Connection Control Program

GSWC's Cross Connection Control Program provides a level of certainty that the water in the company's distribution system is protected from possible backflow of contaminated water from customers' premises. For additional information and how to learn how to prevent cross-connections at your home, visit https://www.gswater.com/protecting-our-drinking-water/.



Flushing

Hydrant flushing is an essential maintenance procedure that all water providers must perform periodically to ensure the water delivered to customers meets state and federal drinking water standards. GSWC is using NO-DES (Neutral Output-Discharge Elimination System) flushing in several of our service areas to help flush our distribution systems sustainably.


Traditional hydrant flushing discharges hundreds of thousands of gallons of water onto the street. GSWC's NO-DES trucks and trailers offer a new maintenance technology, connecting two hydrants to a complex filtration system which cleans the water and returns it to the distribution system.

For more information about hydrant flushing, visit http://www.gswater.com/flushing.

If You Have Questions - Contact Us

For information about your water quality or to find out about upcoming opportunities to participate in public meetings, please contact our 24-hour Customer Service Center at **1.800.999.4033**. Visit us online at www.gswater.com or email us at customerservice@gswater.com.

Este informe contiene información muy importante sobre su agua de beber. Tradúzcalo o hable con alguien que lo entienda bien.



Connect with us to learn more!

Visit www.gswater.com to:

- ♦ Access the latest Water Quality Report for your area
- Get the latest updates and news regarding water supply and state/local restrictions
- Learn more about water-use efficiency, including programs and rebates in your area
- Understand your water bill and learn about payment options
- Obtain information about programs for low-income customers (Customer Assistance Program or CAP)
- Sign up to receive email updates about your water service





Infrastructure Investments

At GSWC, we believe access to clean and reliable drinking water is a fundamental right for all Californians. Our customers should never think twice about the quality of water coming from their taps. To fulfill this commitment, we continue to invest in water infrastructure essential to treating and delivering sustainable, long-term value for our customers.

Since 2019, GSWC has invested more than \$894 million in water infrastructure projects essential to providing quality, reliable water to over 1 million Californians in 81 communities. In 2024, GSWC invested more than \$210 million in water treatment facilities, water storage and distribution systems. GSWC continues to invest in its water system, which now includes approximately 2,869 miles of pipeline, 81,073 valves and 27,118 fire hydrants. These proactive investments in local infrastructure avoid the costly and sometimes dangerous effects of deferring maintenance or delaying the replacement of aged infrastructure.

Customers interested in learning more about current and completed infrastructure projects in their service areas are encouraged to visit their service area's webpage at www.gswater.com/your-service-area.

Conserving for California

After years of severe drought, California's water supply has improved for many parts of the state. GSWC customers did a tremendous job reducing water use during the last drought, and most have continued those water-efficient practices and made conservation a way of life. GSWC is proud to be your partner in conservation, offering tips and programs to help you manage your water use and control your bill. To learn more about conservation programs and rebates in your area, please visit www.gswater.com/conservation or call 1.800.999.4033.



A drought-tolerant garden.